

**DECLARATION OF PERFORMANCE**  
**MEDITE PREMIER FR EUROCLASS B**  
Reference Number: **CEDOP11**  
**MEDITE EUROPE DAC**  
**Redmondstown, Clonmel**  
**County Tipperary, Ireland**

| Product Type  | Intended Use  | AVCP* | Notified Body Reference |
|---|---|-------|-------------------------|
| MDF   | Internal use as non-structural components in dry conditions | 1     | EFFECTIS France<br>1812 |
| *Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011 |   |       |                         |

**Declared Performance**

| Essential characteristics                                | Performance   |         | Harmonised technical specification |
|--|---|---------|------------------------------------|
| Thickness Range (mm)                                     | 4 to 6  | >6 to 9 | EN 13986:2004:A1:2015              |
| Internal bond (N/mm <sup>2</sup> )                       | 0.65  | 0.65    |                                    |
| Swelling in thickness (24hr) %                           | 30  | 17      |                                    |
| Release of formaldehyde                                  | E1  | E1      |                                    |
| Reaction to fire   | B-s2,d0   | B-s2,d0 |                                    |
| Reaction to fire:<br>Field of application                | Valid with or without horizontal and vertical butt joints.<br>Valid with an air gap up to 40mm.<br>Valid on any substrate with thickness ≥ 9mm, of fire performance A2-s2, d0 or better, and density ≥ 652.5kg/m <sup>3</sup> . |         |                                    |
| Airborne sound insulation (R)                            | NPD   | NPD     |                                    |
| Sound absorption Frequency range<br>250Hz to 500Hz (α)   | NPD   | NPD     |                                    |
| Sound absorption Frequency range<br>1000Hz to 2000Hz (α) | NPD   | NPD     |                                    |
| Thermal conductivity                                     | NPD   | NPD     |                                    |
| Biological Durability                                    | Use Class 1   |         |                                    |
| Release (content) of pentachlorophenol (PCP)             | ≤5ppm   | ≤5ppm   |                                    |

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Guillaume Coste, Technical Services Manager.

Clonmel, Ireland. 11/09/2025